

Model: HR250

Rev. B1.00+

Blade Wheel Power:

HR250SEB25U 25HP, 240V 3ph
HR250SEC25U 25HP, 480V 3ph

Material Capacities:

Min. Material Width: 1-1/2"
Max. Material Width: 16"
Min. Material Length: 36"
Max. Material Length: N/A
Max. Material Height: 12"
Min Cut Height (lower head): 1/2"
Max Cut Height (lower head): 7"
Min Cut Height (upper head): 1"
Max Cut Height (upper head): 10-1/2"

Conveyor:

Conveyor Surface: 15-1/2"x106"
Conveyor Belt: 215"
Feed Speed - Variable: 0-90 ft/min
Conveyor Power Selections: 2HP

Blades:

Blade Length: 178" 7/39 Turbo, 7/8" Spacing recommended.
Blade Width: 1-1/4" or 1-1/2" or 2" 1-1/4" is standard, 1-1/2" requires rollers, 2" requires rollers and 2" blade wheels
Blade Thickness: 0.042" or 0.055"
Blade Wheel Diameter: 28"
Blade Wheel Type: Steel, Dynamically Balanced

Machine Dimensions:

Packing Dimensions: 80"x114"
Length: 107-5/8"
Width: 95-3/8"
Height: 75-7/8"
Weight: 4715lbs
Dust Collection Port Size: 6" All (3x)
Country of Manufacture: USA