

Model: CPI-XXC-XXXX

Rev. A1.00+

Power:

Electric Power Options: 2HP 240V/60Hz 3Ph
2HP 480v/60Hz 3Ph
2HP 220v/60 HzZ 1Ph

Horizontal Length: 10', 15', 20', 30'
5' Inclined section

Deck Width: 54"

Feed Chains: 4 Strand HD #2060 Roller Chain

Feed Rate: 15'/min - 60'/ min

Height: Flat section: 34" (+/-1" adjustability)
Inclined section: Low end - 24", High end - 34" (+/-1" adjustability)

Material Handling and Pallet Industry

Alpha Numeric Identification

CPx-LENGTH(TYPE)-POWER

CP: Material Handling, Pallet Industry Prefix

x: **I** - Will pair with **C** (chain) Conveyor, identifying inclined in-feed

S - Will pair with **B** (belt) Coveyor, identifying two separate drives (horizontal and inclined)

LENGTH: Length of material handling (5ft. Increments; total of horizontal sections)

TYPE: **C**- Chain, **B** - Belt

POWER: **EA** - 240V, 1Ph

EB - 240V, 3Ph

EC - 480V, 3Ph

EBC - 240/480V, 3Ph **EAM** - 120/240V, 1Ph

Ex: CP-30C-EC2U Conveyor - 30' Chain; 480V, 3PH

CPS-35B-EC4U Conveyor - 35' Belt Material; 480V, 3PH

CP-10B-EBC2U Conveyor - 10' Belt; 240/480V, 3PH