

Model: G25/E15/D22/D26 Rev. A2.00 - A2.02**Dimensions**

Length For Travel (Hitch to Lights): 13' 9"
 Length For Opertion (with Outfeed Table): 20' 6"
 Width (Fender to Fender): 6' 4"
 Height (with Trailer): 4' 3"
 Bed Height (Ground to Bed): 31"
 Infeed Table Length: 6' 5"
 Outfeed table Length: 10'

Weight:	G25	E15	D22
Basic Unit:	2020 lbs.	2020 lbs	2200 lbs.

Trailer
Axle Capacity: 2500 lbs.
Tire Capacity: 1870 lbs.
Tire Size: ST205/75R

Capacity:
Max. Board Width: 24"
Max. Cut: 15"
Min. Cut: 3"
Max. Board Thickness: 2 3/8"
Min. Board Thickness: 1/4"

Misc Specifications
Blade Diameter: 14"
Blade Bore: 3"
Blade Kerf (8 Tooth/18 Tooth): .150/.165

Engine/Motor:	G25	E15	D22
Fuel/Energy:	Gas	3-Phase	Diesel
Make:	Kohler	Baldor	Kubota
HP Rating:	25HP	15HP	22HP
RPM-Idle:	1800	N/A	1000
RPM-High (No load):	3600	3450	3000
Noise Level (Operator; not cutting/cutting; dBA):	94/102	82/101	
Noise Level (Puller; not cutting/cutting; dBA):	90/98	78/99	
Blade Speed (No load) RPM:	3000		
Fuel Consumption (Gallon/Clock Hr.):	0.9		
Cooling:	Air	N/A	Water
Engine Drive Shaft O.D. (inches):	1 7/16"	1 3/8"	1 7/16"
Engine Drive Pulley (inches):	6	6	6
Main Driven Pulley (inches):	7	7	6
Drive Belts:	2BX90	2BX90	2BX90
Gear Box Pulleys (Inches):	6"/7"	6"/7"	
Charging System Output (Amp):	15	N/A	65
12V Battery (Cold Cranking Amps @ 32 F):	665	N/A	875
Oil Capacity w/Filter (qts.):	2.1	N/A	5.5

Rates:
Min. Feed Speed: 55 ft./min.
Max. Feed Speed: 70 ft./min.

Electrical Requirements:	EE15 (high voltage)	EE15 (low	EE15-C (Canadian voltage)
Electrical Service:	380V-480V 3-Phase	3-Phase	575V 3-Phase 100A
Fused Disconnect:	30A	60A	30A
Time Delay Fuse:	30A	60A	30A
Suggested Wire Size:	10AWG (50' max.)	max.)	(50' max.)