

Model: G28/E15/D21/D24/D26 Rev. A5.00+**Dimensions**

Length For Travel (Hitch to Lights): 13' 9"
 Length For Opertion (with Outfeed Table): 20' 6"
 Width (Fender to Fender): 6' 4"
 Height (with Trailer): 4' 3"
 Bed Height (Ground to Bed): 31"
 Infeed Table Length: 6' 5"
 Outfeed table Length: 10'

Weight:	G28	E15	D21	D26
Basic Unit:		1870 lbs.		1850 lbs.

Trailer
 Axle Capacity: 2500 lbs.
 Tire Capacity: 1870 lbs.
 Tire Size: ST205/75R

Capacity:
 Max. Board Width: 24.75"
 Max. Cut: 15"
 Min. Cut: 3"
 Max. Board Thickness: 2 3/8"
 Min. Board Thickness: 1/4"
 Min. Board Length: 36"

Misc Specifications
 Blade Diameter: 14"
 Blade Bore: 3"
 Blade Kerf (8 Tooth/18 Tooth): .150/.165

Engine/Motor:	G28	E15	D21	D24	D26
Fuel/Energy:	Gas	3-Phase	Diesel	Diesel	Diesel
Make:	Kohler	Baldor	Yanmar	Yanmar	Caterpillar
HP Rating:	28HP	15HP	21.9HP	24HP	26HP
RPM-Idle:		N/A			1900-2000
RPM-High (No load):		3450	3600		3000
Noise Level (Operator; not cutting/cutting; dBA):		82/101			
Noise Level (Puller; not cutting/cutting; dBA):		78/99			
Blade Speed (No load) RPM:					
Cooling:	Air	N/A	Water	Water	Water
Engine Drive Shaft O.D. (inches):	1 1/8"	1 3/8"	1 1/8"	1 7/16"	1 7/16"
Engine Drive Pulley:	3V4.75X3	3V4.75X3	3/5V44	3/5V44	3/5V49
Main Driven Pulley:	3V6.9X3	3V6.9X3	3/5V670	3/5V670	3/5V670
Drive Belts:	3/3VX900	3/3VX900	3/5VX850	3/5VX850	3/5VX900
Gear Box Pulley:	3V450SH	3V450SH	3V450SH	3V450SH	3V450SH
Blade Shaft/Gear Box Pulley:	3V500SH	3V500SH	3V500SH	3V500SH	3V500SH
Charging System Output (Amp):		N/A	40	40	65
12V Battery (Cold Cranking Amps @ 32 F):	665	N/A	875	875	875
Oil Capacity w/Filter (qts.):		N/A	1.79	3	5.5

Rates:
 Min. Feed Speed: 55 ft./min.
 Max. Feed Speed: 70 ft./min.

Electrical Requirements:	EE15 (high voltage)	EE15 (low voltage)	EE15-C (Canadian voltage)
Electrical Service:	380V-480V 3-Phase 100A	208V-240V 3-Phase	575V 3-Phase 100A
Fused Disconnect:	30A	60A	30A
Time Delay Fuse:	30A	60A	30A
Suggested Wire Size:	10AWG (50' max.)	6AWG (100' max.)	(50' max.)