## Model: LT30 Rev. G9.00 - H4.00

Dimensions:			
	Length:	21'-11"	
	Width:	6'-6"	
	Height (Ground To Mast):	7'-8"	
	Height (Max Head Position):	10'-1"	
	Bed Height (Ground To Bed):		
	Blade Length:		
Wainhta	2.000 10.1g.	G25	D33
Weights:			
	Basic Unit (Wet):		2332 lbs
	With Trailer:		2654 lbs
	Tongue Weight:	123 lbs	103 lbs
Trailer:			
	Axle Capacity:	3500 lbs	
	Tire Capacity:		
		ST215/75R14	
		322 lbs	
Log Consoitu			
Log Capacity:	L s s sth	101.01	
	Length:		
	Length (w/Operator Seat Option):		
	Diameter:	36"	
	Weight:	4400 lbs	
	Max Clamp Width (from stop block):		
	Max Throat Width (guide to guide):		
Max C	ant Width (outer guide to stop block):	25"	
			<b>D</b> 00
Engine:	•• •	G25	D33
	Manufacturer:		Kubota
	Fuel:		Diesel
	Horsepower Rating:	25	33
	Weight:		419
	Idle Speed:		1500 RPM
	High Throttle Speed (No Load):		3200 RPM
			5200 IXI IVI
	Noise Level @		
	Noise Level - @ operator position:		102 dBA
	Noise Level - 20 feet away:		84 dBA
	Blade Speed (No Load):	5330 sfpm	5700 sfpm
	Fuel Consumption (per hour):	0.78 Gal.	1.0 Gal.
	Cooling System:		Water
	Coolant Capacity:		1.75 Gal.
	Drive Shaft O.D.:		1 9/16"
	Drive Pulley:		4.55"
	Drive Belt:		3BX72
	Blade Braking:	1 Second	1 Second
	Oil Capacity w/Filter:	2.1 qts.	6.5 qts
	Batterv:	12V 875CCA	12V 875CCA
	Alternator Output:		140 Amp
	Alternator Belt:		6PK425
Potos:			D33
Rates:		G25	
	Forward (no cutting):		139 ft./min.
		148 ft./min.	148 ft./min.
	Up (24"):	22.3 sec.	23.4 sec.
	Down (24"):	14.8 sec.	14.8 sec.
Hourly Prod	uction (Average range w/experienced		
	operators/average size logs):		
0	operators average size 1095).		
Options:	<b>.</b>		
	Single/Lap Siding Option:		
	Manual Turner:	143 lbs	
	Manual Toeboards:	44 lbs	
	Manual Winch:	17 lbs	
	Debarker:		
	Resaw Attachment:		
	Laser Sight:		
	Setworks:	13 lbs	
	6' Bed Extension:	390 lbs	
	12' Bed Extension:	758 lbs	
	24' Bed Extension:		
	Operator Seat:		
	LubeMizer:		
	LubeivilZer	12 105	

## Model: LT40 Rev. H1.00-H5.00

Dimensions:			
	Length:		
	Width:		
	Height (Ground To Mast):	7'-8"	
	Height (Max Head Position):		
	Bed Height (Ground To Bed):		
	Blade Length:	158"	
Weights:		G25	D33
•	Basic Unit (Wet):	2390 lbs	2532 lbs
	With Trailer:		2854 lbs
	Tongue Weight:		95 lbs
Trailer:			
maner.	Ayla Canacity	2500 lbc	
	Axle Capacity:		
	Tire Capacity:		
		ST215/75R14	
	0	322 lbs	
Log Capacity:			
	Length:		
	Length (w/Operator Seat Option):	18'-11"	
	Diameter:	36"	
	Weight:	4400 lbs	
	Max Clamp Width (from stop block):		
	Max Throat Width (guide to guide):		
Max C	ant Width (outer guide to stop block):	25"	
			D33
Engine:	N#=f= -1	G25	D33
	Manufacturer:		Kubota
	Fuel:		Diesel
	Horsepower Rating:	25	33
	Weight:	130	419
	Idle Speed:	1800 RPM	1500 RPM
	High Throttle Speed (No Load):		3200 RPM
	· · · · · · · · · · · · · · · · · · ·		
	Noise Level - @ operator position:	92 dBA	102 dBA
	Noise Level - 20 feet away:		84 dBA
	Blade Speed (No Load):		5700 sfpm
	Fuel Consumption (per hour):		1.0 Gal.
			Water
	Cooling System:		
	Coolant Capacity:		1.75 Gal.
	Drive Shaft O.D.:		1 9/16"
	Drive Pulley:		4.55"
	Drive Belt:	2BX71	3BX72
	Blade Braking:	1 Second	1 Second
	Oil Capacity w/Filter:		6.5 qts
		12V 875CCA	12V 875CCA
	Alternator Output:		140 Amp
	Alternator Belt:		6PK425
Rates:		G25	D33
natos.	Forward (no cutting):		139 ft./min.
		148 ft./min.	148 ft./min.
		22.3 sec.	23.4 sec.
	Down (24"):		14.8 sec.
Hourly Prod	uction (Average range w/experienced		
	operators/average size logs):		
Options:	- • • • •		
	Single/Lap Siding Option:	0 lbs	
	Manual Turner:		
	Manual Toeboards:		
	Manual Winch:		
	Debarker:		
	Resaw Attachment:		
	Laser Sight:	2.5 lbs	
	Setworks:	13 lbs	
	6' Bed Extension:		
	12' Bed Extension:		
	24' Bed Extension:		
	Operator Seat:		
	LubeMizer:	12 IDS	