Dimensions:		Metric	Wide Saw Head Only:	
Length: 2	26'-4"	8.02m	26'-4"	
Width: 6		1.97m	7'-1/2"	
Height (Ground To Mast): 7		2.26m	7'-5"	
Height (Max Head Position): 9		3m	9'-10"	
Bed Height (Ground To Bed): 3		0.78m	30 3/4"	
Blade Length: 1		4.01m	171"	
Weights:				
Basic Unit with Trailer(with heaviest power option):				
` Tongue Weight:				
Trailer:				
Axle Capacity: 3	3500 lbs	1587kg		
Tire Capacity: 1	1870 lbs	848.2kg		
Tire Size: S	ST215/75R14	0		
Cutting Capacity:			Wide Saw Head Only:	
Length: 2		6.4m	21'	
Diameter: 3	36"	0.91m	36"	
Maximum Log Weight: 4	1400 lbs	1995kg	4400 lbs	
Max Clamp Width (from stop block): 2	26"	0.66m	26"	
Max Throat Width (guide to guide): 2	27 1/2"	0.7m	34"	
Max Cant Width (outer guide to stop block): 2	24 3/4"	0.63m	31 1/4"	
Min. Cut Height: 1	"	25.4mm	1"	
Max. Cut Height: 3	35 1/4"	0.9m	35 1/4"	
Maximum Throat Depth: 1	11 1/4"	0.28m	11 1/4"	
Power Unit: C	G38	D35	D47	E25
Manufacturer: k	Kohler	Yanmar	Yanmar	Lincoln
Fuel: g	jas	Diesel	Diesel	Electric
Horsepower Rating*: 3	35	35	47.5	25
Weight (lbs)*: 1	132	345	400	
Cooling System*: a	air	water	water	air
Noise Level (dba)*: 1	100-105(@3000 rpm)	89	89	
Engine Oil & Type*:	、 · · /			
Engine Oil Capacity w/Filter*:				
Temperature Range & Oil Grades*:				
Coolant Capacity*:				
Rates:				
Max. Forward (Not Cutting): 2				
Reverse: 2 Hourly Production (Average range w/experienced e				
operators/average size logs):				

operators/average size logs):

*Manufacturer's specification