Dimensions:	Metric	Wide Saw Head Only:	
Length: 26'-4"	8.02m	26'-4"	
Width: 6'-6"	1.97m	7'-1/2"	
Height (Ground To Mast): 7'-5"	2.26m	7'-5"	
Height (Max Head Position): 9'-10"	3m	9'-10"	
Bed Height (Ground To Bed): 30 3/4"	0.78m	30 3/4"	
Blade Length: 158"	4.01m	171"	
Veights:			
Basic Unit with Trailer(with heaviest power option): Tongue Weight:			
Frailer:			
Axle Capacity: 5200 lbs	2358kg		
Tire Capacity: 2540 lbs	1152kg		
Tire Size: ST225/75R15			
Cutting Capacity:		Wide Saw Head Only:	
Length: 21'	6.4m	21'	
Diameter: 36"	0.91m	36"	
Maximum Log Weight: 4400 lbs	1995kg	4400 lbs	
Max Clamp Width (from stop block): 26"	0.66m	26"	
Max Throat Width (guide to guide): 27 1/2"	0.7m	34"	
Max Cant Width (outer guide to stop block): 24 3/4"	0.63m	31 1/4"	
Min. Cut Height: 1"	25.4mm	1"	
Max. Cut Height: 35 1/4"	0.9m	35 1/4"	
Maximum Throat Depth: 11 1/4"	0.28m	11 1/4"	
Power Unit: G38	D35	D47	505
			E25
Manufacturer: Kohler	Yanmar	Yanmar	Lincoln
Fuel: gas	Diesel	Diesel	Electric
Horsepower Rating*: 35	35	47.5	25
Weight (lbs)*: 132	345	400	
Cooling System*: air	water	water	air
Noise Level (dba)*: 100-105(@3000 rpm) 89	89	
Engine Oil & Type*:			
Engine Oil Capacity w/Filter*:			
Temperature Range & Oil Grades*:			
Coolant Capacity*:			
Rates:			
Max. Forward (Not Cutting): 200 ft/min			
Reverse: 215 ft/min			
Hourly Production (Average range w/experienced 675 bd ft/hr			
operators/average size logs):			

*Manufacturer's specification