| Dimensions:   | Metric   | Wide Saw Head Only: |
|---|----------|---------------------|
| Length: 26'-4"  | 8.02m    | 26'-4"              |
| Width: 7'-2"  | 2.18m    | 7'-8" (2.33m)       |
| Height (Ground To Mast): 7'-6"                                      | 2.28m    | 7'-6"               |
| Height (Max Head Position): 10'-4"                                  | 3.05m    | 10'-4"              |
| Bed Height (Ground To Bed): 29 1/2"                                 |          | 29 1/2"             |
| Blade Length: 184"  | 4.67m    | 196" (4.97m)        |
| Weights:  |          |                     |
| Basic Unit with Trailer(with heaviest power option): Tongue Weight: |          |                     |
| Trailer:  |          |                     |
| Axle Capacity (LT70 Electric Remote): 5040 lb                       | •        |                     |
| Tire Capacity (LT70 Electric Remote): 2835 lb                       |          |                     |
| Tire Size (LT70 Electric Remote): LT225/                            |          |                     |
| Axle Capacity (LT70 Diesel Remote): 6000 lb                         |          |                     |
| Tire Capacity (LT70 Diesel Remote): 3230 lb                         |          |                     |
| Tire Size (LT70 Diesel Remote): 8-14.5                              | 12PR     |                     |
| Cutting Capacity:   |          | Wide Saw Head Only: |
| Length: 20'-2"  | 6.14m    | 20'-2"              |
| Diameter: 36"   | 0.91m    | 36"                 |
| Maximum Log Weight: 4400 lb   | _        | 4400 lbs            |
| Max Clamp Width (from stop block): 26"                              | 0.66m    | 26"                 |
| Max Throat Width (guide to guide): 28 1/2"                          | 0.72m    | 34 1/2"             |
| Max Cant Width (outer guide to stop block): 25 5/8                  | 0.65m    | 31 5/8"             |
| Min. Cut Height: 1"   | 25.4mm   | 1"                  |
| Max. Cut Height: 35 3/16  | 5" 0.9m  | 35 3/16"            |
| Maximum Throat Depth: 12 3/4"                                       |          | 12 3/4"             |
| Power Unit: D55   | E25      | E30                 |
| Manufacturer: Yanma   |          | Lincoln             |
| Fuel: Diesel  | Electric | Electric            |
|   | 25       | 30                  |
| Horsepower Rating*: 55.5  | 25       | 30                  |
| Weight (lbs)*: 395  | 0:-      | o i r               |
| Cooling System*: water  | air      | air                 |
| Noise Level (dba)*: 72  |          |                     |
| Fuel Consumption(gallon/hour)*: 1                                   |          |                     |
| Engine Oil & Type*:   |          |                     |
| Engine Oil Capacity w/Filter*:                                      |          |                     |
| Temperature Range & Oil Grades*:                                    |          |                     |
| Coolant Capacity*:  |          |                     |
| Rates:  |          |                     |
| Max. Forward (Not Cutting): 190 ft/r                                | nin      |                     |
| Reverse: 200 ft/r   |          |                     |
| Hourly Production (Average range w/experienced 940 bd               |          |                     |
| Houry Froduction (Average range w/expension 940 ha                  |          |                     |

<sup>\*</sup>Manufacturer's Specification