Dimensions:		Metric	Wide Saw Head Only:
	Length: 26'-4"	8.02m	26'-4"
	Width: 7'-2"	2.18m	7'-8" (2.33m)
	Height (Ground To Mast): 7'-6"	2.28m	7'-6"
	Height (Max Head Position): 10'-4"	3.05m	10'-4"
	Bed Height (Ground To Bed): 29 1/2"	0.75m	29 1/2"
	Blade Length: 184"	4.67m	196" (4.97m)
Weights:			
=	with Trailer(with heaviest power option):		
	Tongue Weight:		
Trailer:			
	Axle Capacity: 5040 lbs	2286kg	
	Tire Capacity: 2835 lbs	1285kg	
	Tire Size: LT225/75/R16	3E	
Cutting Capacity:			Wide Saw Head Only:
	Length: 20'-2"	6.14m	20'-2"
	Diameter: 36"	0.91m	36"
	Maximum Log Weight: 4400 lbs	1995kg	4400 lbs
	Max Clamp Width (from stop block): 26"	0.66m	26"
	Max Throat Width (guide to guide): 28 1/2"	0.72m	34 1/2"
Мах	x Cant Width (outer guide to stop block): 25 5/8	0.65m	31 5/8"
	Min. Cut Height: 1"	25.4mm	1"
	Max. Cut Height: 35 3/16"	0.9m	35 3/16"
	Maximum Throat Depth: 12 3/4"	0.32m	12 3/4"
Power Unit:	D55		
	Manufacturar: Vanmar		

Manufacturer: Yanmar

Fuel: Diesel

Horsepower Rating*: 55.5 Weight (lbs)*: 395

Cooling System*: water

Noise Level (dba)*: 72

Fuel Consumption(gallon/hour)*: 1

Engine Oil & Type*:

Engine Oil Capacity w/Filter*:

Temperature Range & Oil Grades*:

Coolant Capacity*:

Rates:

Max. Forward (Not Cutting): 200 ft/min

Reverse: 200 ft/min

Hourly Production (Average range w/experienced 940 bd ft/hr

operators/average size logs):

^{*}Manufacturer's Specification